



**OPEN
SWEEPERS
AM 210 OS
AM 250 OS
AM 300 OS**

**Incredibly
clean outcome**



The AM open sweepers are ideally suited for versatile working environment because of their excellent brushing qualities and technical features. Incredibly clean outcome is guaranteed by the amazing floating mechanism that presses and adjusts the brush automatically.



ROAD INTELLIGENCE

Fast road cleaning

You can easily attach the AM open sweepers to tractors, wheel loaders, and trucks using their standard attachment method. The floating mechanism is equipped with a vibration block and shock protection, which efficiently absorbs the vibration caused by the brush. Additionally, it protects the machine and makes the driver's work much easier and more comfortable.

The effective brushing angle adjustment increases the working width considerably, making the brush a lot more versatile. Dust can be kept to a minimum with the effective watering nozzles, which come as accessories. This improves the outcome substantially. Our open sweepers always utilise the basic machine's brushing speed, which makes them extremely cost-efficient.



Pictures may contain accessories.

Technical information	AM 210 OS	AM 250 OS	AM 300 OS
Working width	2,100 mm	2,500 mm	3,000 mm
Maximum width	2,176 mm	2,576 mm	3,076 mm
Weight	415 kg	450 kg	550 kg
Brushing angle	25°/25°	25°/25°	25°/25°
Hydraulic motors	1	1	2
Required volume flow	50 l/min	50 l/min	90 l/min
Brush disks	43	51	63

HYDRAULICS

Double acting lifting cylinder	1
Double acting swivelling cylinder	1
Oil consumption	50–90 l/min
Working pressure	180 bar

Head Office:

Arctic Machine Oy, Karsikonmäentie 1, FI-77800 Iisvesi, Finland
 Tel. +358 (0)20 7791 500, fax +358 (0)20 7791 501
 am@arcticmachine.com, www.arcticmachine.com

Copyright © Arctic Machine Oy. All rights reserved.

