



ROLLER SPREADERS AM 1600 RS AM 2500 RS

**Professional
antiskid
treatment**



The AM 1600 RS and AM 2500 RS roller spreaders are designed for spreading salt, sand, and other coarse antiskid material. Their sturdy frame, state-of-the-art technical solutions, and high reliability make them especially suitable for heavy professional use.



ROAD INTELLIGENCE

Cost efficient and safe

You can easily attach the AM 1600 RS and AM 2500 RS roller spreaders to a traction device. Thanks to their big tyres, they are easy to pull. The spreaders are also both safe and cost effective; they enhance road safety and at the same time reduce the amount of antiskid material needed in road maintenance.

You can fine-tune the material flow from the spreading roller to the ground hydraulically. You can also easily perform the rough adjustment with the adjustment screw and the regulation valve of the flow. The galvanized anti-corrosion frame as well as the sturdy axles and hubs ensure that the spreaders continue to work well even in heavy use.



Pictures may contain accessories.

Technical information	AM 1600 RS	AM 2500 RS
Capacity	1,600 l	2,500 l
Working width	1,500 mm	2,000 mm
Required hydraulic flow, max.	50 l/min	50 l/min
Max. hydraulic pressure	200 bar	200 bar
Height	1,550 mm	1,550 mm
Tyres	11.5/80-15.3	11.5/80-15.3
Frame material	Hot-dip galvanized	Hot-dip galvanized
Weight when empty	680 kg	780 kg

Head Office:

Arctic Machine Oy, Karsikonmäentie 1, FI-77800 Iisvesi, Finland
Tel. +358 (0)20 7791 500, fax +358 (0)20 7791 501
am@arcticmachine.com, www.arcticmachine.com

Copyright © Arctic Machine Oy. All rights reserved.

