



SIDE- MOUNTED PLOUGH FOR TRACTORS AM 207 TR

Perfect road
maintenance



With the AM 207 TR side-mounted plough, you can easily increase the ploughing width of your tractor. In addition to ploughing, you can use it for removing windrow and lowering snow banks when levelling packed snow. During springtime, you can also remove snow banks. This speeds up road drying and thus substantially reduces road maintenance costs.



ROAD INTELLIGENCE

Effective and safe winter road maintenance

With a side-mounted plough, you can control the ploughing width of your tractor, which decreases the size of the snow banks on the road. Moreover, the whole road width stays safe for traffic. You can also use the plough to decrease and remove snow banks at intersections, which significantly improves visibility.

The plough's three-point linkage makes big movements of the wing possible. These are necessary for controlling the snow bank size on curbs. We've taken into account the special characteristics of snow when designing the plough's wing.



Pictures may contain accessories.

Technical information	AM 207 TR
Max. ploughing width	1,510 mm
Wing tip height	550 mm
Max. wing height	1,160 mm
Plough angle adjustment	0–45°
Inclination angle adjustment	0–13°
Blade angle	42°
Blade attachment	2,135 mm
Length x width x height	2,350 x 2,840 x 1,320 mm
Weight	1,200 kg
Swivelling cylinder	1
Inclination cylinder	1
Oil consumption	30 l/min
Pressure	100 bar

Head Office:

Arctic Machine Oy, Karsikonmäentie 1, FI-77800 Iisvesi, Finland
Tel. +358 (0)20 7791 500, fax +358 (0)20 7791 501
am@arcticmachine.com, www.arcticmachine.com

Copyright © Arctic Machine Oy. All rights reserved.

